

Lighting Specifications

The McFarlin Memorial Auditorium

House Dimmers

ETC Sensor	288 dimmers
∞	288 @ 2.4 K
∞	Raceway and drop box combinations

Control Board

Control board is an *ETC Insight 3x*. The board has a capacity of 9,999 cues per show with 1,000 control channels; 500 groups and 108 overlapping submasters with programmable effects (using Emphasis server). The memory mode records/playsback with timed cross fades and split fades. Board is capable of operating color scrollers, intellibeams, cyberlights, e.t.c. Console is located on the main floor seating level in the light booth at the rear of house. Board is running Emphasis software. Board will except Expression and Insight formats.

There are three disconnects for road hook-ups: total of 2100 amps.

- ∞ 100 amp. X 3 phase
- ∞ 200 amp. X 3 phase
- ∞ 400 amp. X 3 phase

Lighting Inventory

Strand Century 10" lekos (FOH)		1K 6
Strand Century 8" lekos (FOH)		1K 24
Strand Century 6x9 lekos	750w	18
Source 4-36°	575w	50
Source 4-26°	575w	50
Source 4-19°	575w	20
Altman 6 x12 lekos	750w	54
Altman 6 x9 lekos	750w	36
Altman 8" fresnels	1K	27
Kligle 6" fresnels	750w	12
Cyc 4 circuit CCD	500w	12
Strips 4 circuit, 8'	150w	20
Par 64 - med flood	1K	28
Par 64 - narrow	1K	6
Par 64 - wide	1K	6
Ground row 4 circuit, T-3	300W	8
Xenon Super Troupers	1600w	2 (fixed)
Two-fers		50
Assorted jumpers		varies
6 channel multicable	50'	2
6 channel multicable	25'	2

Note: Stage uses 3-pin stage connectors

Spotlights

2 Super Trooper Long Throw Follow Spots
With Radiance Super Trooper Color Changer